



FW= Frame width  
 Min. 1800 / max. 3000  
 Alt. F FW=2COW+36+X  
 Alt. U FW=2COW+32+X

FH= Frame height  
 Min. 2100 / max. 3150

X= Distance to avoid finger trap (25 mm)

COW= Clear opening width  
 Alt. F COW=(FW-36-X)/2  
 Alt. U COW=(FW-36-X)/2+2

COH= Clear opening height  
 COH=FH-195

CL= Cover length

State when ordering  
 FW=.....mm  
 FH=.....mm  
 X=.....mm  
 COW=.....mm  
 COH=.....mm  
 Cover  
 CL=.....mm

Profile option  
 Alt. F (concrete/brick)  
 Alt. U (aluminium/steel)

Surface treatment  
 Silver anodized  
 Special anodized.....  
 RAL.....  
 Special powder coating.....  
 .....

Glass  
 6/10/6 Insulated laminated glass

Lock  
 Floor lock Euro 1-way  
 Floor lock Euro 2-way

Scale 1:5

Customer: \_\_\_\_\_

Door id: \_\_\_\_\_

Project No: \_\_\_\_\_

EntreMatic ref: \_\_\_\_\_

Date: \_\_\_\_\_

Sign: \_\_\_\_\_

**Profile system**  
**EMPS Thermo with EMSL**  
**2 Panel beam mounted right**

**ENTRE MATIC**

2 833010